



NOTES:

1. POSTS SHALL BE GALVANIZED STEEL - 14 GAUGE STRAIN POSTS & 20 GAUGE INTERMEDIATE POSTS.
2. WIRE SPACING SHALL NOT EXCEED 3.5 INCHES WITH A MINIMUM 26 WIRE SYSTEM.
3. WIRE TERMINATIONS SHALL BE MADE TO STRAIN POSTS USING RATCHETING BRACKET THAT IS CAPABLE OF A LATERAL CHANGE IN DIRECTION OF UP TO 45 DEGREES.
4. EACH WIRE STRAND SHALL HAVE A SPRING, ALLOWING THE WIRE TO ADJUST TO VARIATION IN TEMPERATURE.
5. SYSTEM SHALL BE ARMED BY ALTERNATING PULSE THROUGH EVERY OTHER WIRE, PULSE HIGH SETTING SHALL BE 8000 KV.
6. ALL TERMINAL POSTS SHALL BE PROPERLY BRACED TO SUPPORT STRAIN POSTS.

ELEVATION VIEW

Unless Noted Otherwise		DO NOT SCALE OFF DRAWING		PROPRIETARY INFORMATION	
.x	Decimal ± .040			This drawing is the proprietary property of AMERISTAR, Tulsa, OK and must not be duplicated or used in whole or in part for the making of drawings, prints or parts to the detriment of, or harm to, the owner. In accepting this drawing, the recipient agrees to keep the information contained confidential.	
.xx	Decimal ± .030				
.xxx	Decimal ± .020				
.xxxx	Decimal ± .010	Angular ± 0.5°			
.xxxxx	Decimal ± .010				
REVISION HISTORY					
REV	ECN	AUTHOR	DATE	DESCRIPTION	
				TITLE: PULSE DEFENSE ELEVATION DRAWING 8' H W/ 6' CHAINLINK	
				DATE: 9/14/16	SHEET: 1 of 1
				DRN BY: TLS	REV: a
				DRAWING NO: 99-900-1542	

